



Detail Specifications

Weights: 1-Stainless Steel Unit

- Shipping weight = 14.1 ounces
- Unit with all components = 11.83 ounces
- Unit with all components (#2 philips screw bit and 9/64 drill bit) included = 12.4 ounces

Weights: 1-Aluminum Alloy Unit

- Shipping weight = 8.5 ounces
- Unit with all components = 6 ounces
- Unit with all components (#2 philips screw bit and 9/64 drill bit) included = 8 ounces

Materials:

- 304 Stainless Steel with Black Silicone Rubber Bumpers
- ADC Aluminum Alloy with Black Silicone Rubber Bumpers

Finish:

Natural, with Tumble Polished Latch Base, Catch, and Swing Arm

Door Mounting Location:

Inside (Interior), Opposite Hinge (Lock) Side

Door Swing Type:

Single, Interior Swing

Minimum Wall Clearance:

3.75" (recommended) Consult the manufacturer for applications with less than 3.75" clearance.

Catch Mounting:

Solid Wood or Hollow Steel Doors via Four each 1"¼" #10 Philips head Screws (included)

Latch Base Mounting:

Solid Wood or Hollow Steel Door Frame (Jamb) via Three each 1" #10 Philips head Screws (included)

Features:

- 50% Noise Reduction
- Damage Reduction
- Inadvertent Lockout Protection
- 20 years Design Life

Installation Tools Included:

#2 Philips Screw Bit, 9/64" Drill Bit, Installation Template, Installation Instructions

Installation Tools Required:

Power Drill, ¼" Screw Driver Bit Holder, Center Punch (optional), Tape Measure (optional)